



Application reference guide!

1. Always read the product label before using Raynox®.
2. Raynox® needs to be applied **BEFORE** sunburn occurs. The typical conditions that will induce sunburn are clear calm days with temperature about 30°C and above with LOW relative humidity.

The correct procedure for mixing Raynox® in the spray tank is as follows:

3. Fill the tank with the **ENTIRE WATER VOLUME** that is required

YOU MUST KNOW YOUR WATER HARDNESS! If you do not know your water hardness have it tested prior to using Raynox. For more information please call your Colin Campbell (Chemicals) representative.

4. Add the required amount of water softener for your water hardness.
 - The amount of water softener to add can be found on the product label and the water softener chart available from Colin Campbell (Chemicals) or your local rural merchandise store. It is also available on our website www.campbellchemicals.com.au
5. Agitate the treated water for a few minutes
6. Add the required amount of Raynox® to the treated water, agitate and spray onto crop.
7. Now that the first application has been made **make sure you apply the subsequent Raynox® applications as per the spray intervals on the label.**
8. Immediately after application clean the spray tank and nozzles by flushing with at least 200L of clean water.

A Clear Solution to Sunburn



Raynox is distributed exclusively in Australia by:

Colin Campbell (Chemicals) Pty Ltd
5 Blackfriar Place, Wetherill Park NSW 2164
Ph: (02) 9725 2544
www.campbellchemicals.com.au

RAYNOX® is a registered trademark of FruitGard, LLC. Manufactured by

Pace
International